

## Super Flow Enamel

### PRODUCT DESCRIPTION AND USES:

Super-flow is a smooth, high gloss, long oil alkyd Marine quality enamel that dries moderately fast to form a uniform, tough film. Has very good application properties, and can be used over properly primed metal and timber surfaces. Used as a finishing coat for ship and boat interiors and exterior hulls above the waterline

### PHYSICAL PROPERTIES:

Colour:	Wide range available.	
Gloss Level:	Full gloss, semi-gloss and satin	
Volume Solids:	50%	
Product Density:	1.2 Kg / litre	
Drying Time @ 25°:	Touch dry 4 hours	Hard dry 24 hours
	Recoat 24 hours (min)	Recoat 48 hours (max)

### APPLICATION DATA:

Suitable for application by brush roller or spray.

Recommended

Dry Film Thickness: 50um

Theoretical Spreading Rate @ 50um: 10 sq metres per litre. For optimum performance 2 coats are Recommended.

Thinning: Normally not required for brush or roller application. For spray application up to 20% of T-72 Thinner may be added.

Equipment Cleaning: Clean all equipment immediately after with T-72 Thinner

### **SURFACE PREPARATION:**

Remove all loose and flaking paint from the substrate, surface must be free of contaminants, clean and dry. Apply over recommended undercoat such as Ultra-Coat. If surface is glossy, sand with fine glasspaper

### **STORAGE AND PACKING:**

**Storage:** The Product must be stored in accordance with national regulations. Preferred storage conditions are to keep the containers in a dry space provided with adequate ventilation. The containers should be sealed tightly.

**Packing content:** 1 Litre, 4 Litre 20 Litre.

### **HEALTH AND SAFETY:**

Please observe the precautionary notices displayed on the containers. Spray under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on skin should be removed with suitable cleaner, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

**For detailed information on the health and safety hazards and precautions for use of this product, please refer to the Material Safety Data Sheet.**

**DISCLAIMER:** *The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data with out notice.*

ISSUED SEPTEMBER 2009.  
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED.



Pyramid Paints - Seahorse Marine Paints - 26/B Coburg Road Alberton South Australia 5014  
Phone (08) 83411337 - Fax (08) 3411385